



# HIGH VISIBILITY CUT LEVEL 1 POLYURETHANE DIPPED GLOVES

## BETTER FIT

EN388



3121A



EN388 STANDARDS						
Abrasion	1	2	3	4	-	-
Cut Resistance (Coup Test)	1	2	3	4	5	X*
Tearing	1	2	3	4	-	-
Puncture	1	2	3	4	-	-
Cut Resistance (TDM Test)	A	B	C	D	E	F

\*If the coupe test provides a 3 or above it is marked as an "X" for not applicable and uses the TDM 100 test instead

SMARTWIPE™ Touch  
Screen Compatible  
Palms & Fingertips

Polyurethane  
Grip

High Dexterity  
Fingertips

Breathable Back

Color-Coded Bands  
Easy cut level  
identification



### SPECIFICATIONS

Gauge	15
Liner Material	Polyester Blend Knit
Dip Material	Polyurethane
Cuff Style	Elasticated Knit

### RECOMMENDED APPLICATIONS

- High Dexterity Applications
- Light Material Handling
- Finish Carpentry
- Yard Maintenance
- Plumbing

### CARE INSTRUCTIONS

Machine wash warm water (105°F),  
mild detergent, no bleach.  
Line dry.

SIZE	1 PAIR	12 PAIR (Contractor Pack)
S	48-73-8910	48-73-8910B
M	48-73-8911	48-73-8911B
L	48-73-8912	48-73-8912B
XL	48-73-8913	48-73-8913B
XXL	48-73-8914	48-73-8914B

## SEE MORE PPE



or visit <https://qr.mke.1/2qm6s>

The Milwaukee logo is displayed in white on a red rectangular background. It features the brand name "Milwaukee" in a stylized, cursive font, with a white lightning bolt graphic striking through the letters.

...components  
...ed by

... may be damaged by contacting products containing  
... compatible chemicals. Verify products are chemically compatible  
with ABS/PVC/CPVC.

For important safety and installation information,  
call 800 438-6091 or consult 24-hour  
fax on demand number 800 745-9382.



**Milwaukee**

CUT LEVEL 1

9 1/2 L

SMB0912

